



1111 W. 35th Street
Chicago, IL 60609 USA
Customer Support: (773) 869-1234
www.tripplite.com

Owner's Manual Addendum to #93-1345

OmniPro™ INT 300 & 500 VA

Line Interactive UPS Systems

220/240V, 50/60Hz

ESPAÑOL, DEUTSCH: p. 2

New Specifications

	OmniPro INT 300	OmniPro INT 500
Output Capacity (VA/Watts):	300/185	500/310
Battery Runtime (Half Load/ Full Load) Minutes:	15/5	11/5
Typical Runtime (Desktop PC/15 in. monitor) Minutes:	18	30
Battery Recharge Time:	2-4 hours	2-4 hours
Approvals:	UL, CE	UL, CE
Modem/Fax Protection (starts at 260V):	---	1 line

Nouvelles Caractéristiques

	OmniPro INT 300	OmniPro INT 500
Capacité en sortie (VA/W) :	300/185	500/310
Minutes d'autonomie (batterie à moitié chargée/ pleine charge) :	15/5	11/5
Minutes d'autonomie typique (PC de bureau/moniteur 15 po.) :	18	30
Temps de recharge de la batterie :	2 à 4 heures	2 à 4 heure
Homologations :	UL, CE	UL, CE
Protection modem/fax (début à 260 V) :	---	1 ligne

Especificaciones Nuevos

	OmniPro INT 300	OmniPro INT 500
Capacidad de salida (VA/W):	300/185	500/310
Tiempo de funcionamiento de la batería (Media carga/Carga total) en minutos:	15/5	11/5
Tiempo típico de funcionamiento (PC de escritorio/monitor de 15 pulgadas) en minutos:	18	30
Tiempo de recarga de la batería:	2-4 horas	2-4 horas
Aprobado por las siguientes agencias:	UL, CE	UL, CE
Protección de módem/ fax (comienza a 260 V):	---	1 línea

Neue Technische Merkmale

	OmniPro INT 300	OmniPro INT 500
Ausgangskapazität (VA/W):	300/185	500/310
Batterieautonomie (Halblast/Volllast) Minuten:	15/5	11/5
Durchschnittliche Autonomie (Desktop PC/15-Zoll Monitor) Minuten:	18	30
Batterieaufladezeit:	2-4 Stunden	2-4 Stunden
Zulassungen:	UL, CE	UL, CE
Modem/Fax-Schutz (beginnt bei 260V):	---	1 Leitung